


LOAD TABLES | STANDARD, IMPERIAL

LOAD TABLES - SD

Grating Type: **19W4**
 Design Code: **NAAMM MBG 534**
 Material: **ASTM A1011CS Type B**
 Surface: **Smooth**




U = Safe Uniform Load (lbs/ft²)
 D_u = Deflection Due to Safe Uniform Load (in)
 C = Safe Concentrated Load (lbs/ft of grating width)
 D_c = Deflection Due to Safe Concentrated Load (in)
 Allowable Extreme Fiber Stress = 18 ksi

Bearing Bar Size (inches)	Approx. Weight (lbs/ft ²)	Ped. Span (inches)	Load / Deflection	Span (ft -in)												Section Properties			
				2' - 0"	2' - 6"	3' - 0"	3' - 6"	4' - 0"	4' - 6"	5' - 0"	5' - 6"	6' - 0"	6' - 6"	7' - 0"	7' - 6"	8' - 0"	S _x (in ³)/ft	I _x (in ⁴)/ft	
1" x 1/8"	5.14	51	U	632	404	281	206	158	125									0.211	
			D _u	0.07	0.12	0.17	0.23	0.30	0.38										0.105
			C	632	505	421	361	316	281										
			D _c	0.06	0.09	0.13	0.18	0.24	0.30										
1" x 3/16"	7.33	57	U	947	606	421	309	237	187	152								0.316	
			D _u	0.07	0.12	0.17	0.23	0.30	0.38	0.47									0.158
			C	947	758	632	541	474	421	379									
			D _c	0.06	0.09	0.13	0.18	0.24	0.30	0.37									
1 1/4" x 1/8"	6.23	61	U	987	632	439	322	247	195	158	130							0.329	
			D _u	0.06	0.09	0.13	0.18	0.24	0.30	0.37	0.45								0.206
			C	987	789	658	564	493	439	395	359								
			D _c	0.05	0.07	0.11	0.15	0.19	0.24	0.30	0.36								
1 1/4" x 3/16"	8.98	67	U	1,480	947	658	483	370	292	237	196	164						0.493	
			D _u	0.06	0.09	0.13	0.18	0.24	0.30	0.37	0.45	0.54							0.308
			C	1,480	1,184	987	846	740	658	592	538	493							
			D _c	0.05	0.07	0.11	0.15	0.19	0.24	0.30	0.36	0.43							
1 1/2" x 1/8"	7.33	70	U	1,421	909	632	464	355	281	227	188	158						0.474	
			D _u	0.05	0.08	0.11	0.15	0.20	0.25	0.31	0.38	0.45	0.52						0.355
			C	1,421	1,137	947	812	711	632	568	517	474							
			D _c	0.04	0.06	0.09	0.12	0.16	0.20	0.25	0.30	0.36	0.42						
1 1/2" x 3/16"	10.63	77	U	2,132	1,364	947	696	533	421	341	282	237	202					0.711	
			D _u	0.05	0.08	0.11	0.15	0.20	0.25	0.31	0.38	0.45	0.52	0.59					0.533
			C	2,132	1,705	1,421	1,218	1,066	947	853	775	711	656						
			D _c	0.04	0.06	0.09	0.12	0.16	0.20	0.25	0.30	0.36	0.42	0.48					
1 3/4" x 3/16"	12.27	87	U	2,901	1,857	1,289	947	725	573	464	384	322	275	237	206			0.967	
			D _u	0.04	0.07	0.10	0.13	0.17	0.22	0.27	0.32	0.38	0.45	0.52	0.60				0.846
			C	2,901	2,321	1,934	1,658	1,451	1,289	1,161	1,055	967	893	829	774				
			D _c	0.03	0.05	0.08	0.10	0.14	0.17	0.21	0.26	0.31	0.36	0.42	0.48				
2" x 3/16"	13.92	96	U	3,789	2,425	1,684	1,237	947	749	606	501	421	359	309	269	237		1.263	
			D _u	0.04	0.06	0.08	0.11	0.15	0.19	0.23	0.28	0.34	0.39	0.46	0.52	0.60			1.263
			C	3,789	3,032	2,526	2,165	1,895	1,684	1,516	1,378	1,263	1,166	1,083	1,011	947			
			D _c	0.03	0.05	0.07	0.09	0.12	0.15	0.19	0.23	0.27	0.31	0.36	0.42	0.48			
2 1/2" x 3/16"	17.21	113	U	5,921	3,789	2,632	1,933	1,480	1,170	947	783	658	561	483	421	370		1.974	
			D _u	0.03	0.05	0.07	0.09	0.12	0.15	0.19	0.23	0.27	0.31	0.36	0.42	0.48			2.467
			C	5,921	4,737	3,947	3,383	2,961	2,632	2,368	2,153	1,974	1,822	1,692	1,579	1,480			
			D _c	0.02	0.04	0.05	0.07	0.10	0.12	0.15	0.18	0.21	0.25	0.29	0.34	0.38			

Spans and loads in red exceed a deflection of 1/4" for uniform loads of 100 lbs./sq. ft. Experience has shown that 1/4" deflection is the maximum deflection to give pedestrian comfort, but can be exceeded for other types of loads at the discretion of the specifying professional.

LOAD TABLES - SD

Grating Type: **19W4**
 Design Code: **NAAMM MBG 534**
 Material: **ASTM A1011CS Type B**
 Surface: **Serrated**



U = Safe Uniform Load (lbs/ft²)
 D_u = Deflection Due to Safe Uniform Load (in)
 C = Safe Concentrated Load (lbs/ft of grating width)
 D_c = Deflection Due to Safe Concentrated Load (in)
 Allowable Extreme Fiber Stress = 18 ksi

Bearing Bar Size (inches)	Approx. Weight (lbs/ft ²)	Ped. Span (inches)	Load / Deflection	Span (ft -in)												Section Properties		
				2' - 0"	2' - 6"	3' - 0"	3' - 6"	4' - 0"	4' - 6"	5' - 0"	5' - 6"	6' - 0"	6' - 6"	7' - 0"	7' - 6"	8' - 0"	S _x (in ³)/ft	I _x (in ⁴)/ft
1" x 1/8"	5.14	42	U	355	227	158	116											0.118
			D _u	0.10	0.16	0.22	0.30											0.044
			C	355	284	237	203											
			D _c	0.08	0.12	0.18	0.24											
1" x 3/16"	7.33	46	U	533	341	237	174	133										0.178
			D _u	0.10	0.16	0.22	0.30	0.40										0.067
			C	533	426	355	305	266										
			D _c	0.08	0.12	0.18	0.24	0.32										
1 1/4" x 1/8"	6.23	51	U	632	404	281	206	158	125									0.211
			D _u	0.07	0.12	0.17	0.23	0.30	0.38									0.105
			C	632	505	421	361	316	281									
			D _c	0.06	0.09	0.13	0.18	0.24	0.30	0.30								
1 1/4" x 3/16"	8.98	57	U	947	606	421	309	237	187	152								0.316
			D _u	0.07	0.12	0.17	0.23	0.30	0.38	0.47								0.158
			C	947	758	632	541	474	421	379								
			D _c	0.06	0.09	0.13	0.18	0.24	0.30	0.37	0.37							
1 1/2" x 1/8"	7.33	61	U	987	632	439	322	247	195	158	130							0.329
			D _u	0.06	0.09	0.13	0.18	0.24	0.30	0.37	0.45							0.206
			C	987	789	658	564	493	439	395	359							
			D _c	0.05	0.07	0.11	0.15	0.19	0.24	0.30	0.36	0.36						
1 1/2" x 3/16"	10.63	67	U	1,480	947	658	483	370	292	237	196	164						0.493
			D _u	0.06	0.09	0.13	0.18	0.24	0.30	0.37	0.45	0.54						0.308
			C	1,480	1,184	987	846	740	658	592	538	493						
			D _c	0.05	0.07	0.11	0.15	0.19	0.24	0.30	0.36	0.43						
1 3/4" x 3/16"	12.27	77	U	2,132	1,364	947	696	533	421	341	282	237	202					0.711
			D _u	0.05	0.08	0.11	0.15	0.20	0.25	0.31	0.38	0.45	0.52					0.533
			C	2,132	1,705	1,421	1,218	1,066	947	853	775	711	656					
			D _c	0.04	0.06	0.09	0.12	0.16	0.20	0.25	0.30	0.36	0.42					
2" x 3/16"	13.92	87	U	2,901	1,857	1,289	947	725	573	464	384	322	275	237	206			0.967
			D _u	0.04	0.07	0.10	0.13	0.17	0.22	0.27	0.32	0.38	0.45	0.52	0.60			0.846
			C	2,901	2,321	1,934	1,658	1,451	1,289	1,161	1,055	967	893	829	774			
			D _c	0.03	0.05	0.08	0.10	0.14	0.17	0.21	0.26	0.31	0.36	0.42	0.48			
2 1/2" x 3/16"	17.21	105	U	4,796	3,069	2,132	1,566	1,199	947	767	634	533	454	392	341	300		1.599
			D _u	0.03	0.05	0.07	0.10	0.13	0.17	0.21	0.25	0.30	0.35	0.41	0.47	0.53		1.799
			C	4,796	3,837	3,197	2,741	2,398	2,132	1,918	1,744	1,599	1,476	1,370	1,279	1,199		
			D _c	0.03	0.04	0.06	0.08	0.11	0.13	0.17	0.20	0.24	0.28	0.32	0.37	0.42		

LOAD TABLES - SD IMPERIAL

Spans and loads in red exceed a deflection of 1/4" for uniform loads of 100 lbs./sq. ft. Experience has shown that 1/4" deflection is the maximum deflection to give pedestrian comfort, but can be exceeded for other types of loads at the discretion of the specifying professional.